




RoHS
Compliant
2002/95/EC

REV	LTR	DESCRIPTION	DATE	REVISER	APPD



- NOTES:
- ELECTRICAL:
 - VOLTAGE CURRENT RATING: 2AMP, 30V AC;
 - INSULATION RESISTANCE: 1000MΩ MIN;
 - CONTACT RESISTANCE: 30mΩ MAX;
 - WITHSTANDING VOLTAGE: 500V AC;
 - OPERATING TEMPERATURE: -55°C TO +85°C.
 - Mechanical:
 - Mating Force: 35N MAX
 - Unmating Force: 10N MIN.
 - NOTE: 1. DIMENSIONS MARKED "▼" TO BE CHECKED BY Q.C & IPQC.
 - PART NO.

USAM-04*N-1*S85
 W: WHITE
 B: BLACK
 1: Au 10*
 6: Au 30U*

Bill of materials:

NO	PARTS	MATERIAL	QTY	FINISHING	UNITS	mm	东莞市腾兴电子有限公司				
4	HOUSING	PBT	1	UL94V-0	X. ±0.35	X.* ±2*	SEE NOTE	TITLE: USB A/M 长体直线型弧端小线夹 (四件套)		PART NO.: USAM-04*N-1*S85	
3	UP SHELL	SPCC	1	PLATED NICKEL	.X ±0.3	.X* ±1*		DR: gan 2012/7/04		DWG NO.: AII-S85	
2	DOWN SHELL	SPCC	1	PLATED NICKEL	.XX ±0.25	.XX*	SEE NOTE	CHKD: gan 2012/7/04		SCALE SHEET REV. CUSTOMER 1:1 1/1 B DRAWING	
1	TERMINAL	COPPER ALLOY	4	PLATED GOLD/TIN	.XXX ±0.15	.XXX*		APPD:			
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOVATECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOVATECH INC.											